



## *Sepahan L.Paraffin*

### *Typical Specification*

Property	Value
Flash point (min)	180 - 190 °C
Density @ 15 °C	835 - 840 gr/L
Kin. Vis @ 100°C	3,5 cSt
Water Content	5 ppm
Color	3
Pour Point	-3 °C
Viscosity Index (min)	120

*Head Office: No.1, Nader Alley, East 37<sup>th</sup> St., Alvand Ave., Tehran, IRAN*

*Tel: +9821-88884898 , 88663426*

*Fax: +9821-88774924*

*Web: [www.sepahanoil.com](http://www.sepahanoil.com)*

*Email: [commercial@sepahanoil.com](mailto:commercial@sepahanoil.com)*



## *SEPAX (Sepahan Paraffin Wax)*

### *Typical Specification*

<b>Property</b>	<b>Value</b>
Oil Content	3 – 5 %
Melting Point	60 – 62 °c
Color	<1
Packing	Carton (6*5 kg)

*Head Office: No.1, Nader Alley, East 37<sup>th</sup> St., Alvand Ave., Tehran, IRAN*

*Tel: +9821-88884898, 88663426*

*Fax: +9821-88774924*

*Web: [www.sepahanoil.com](http://www.sepahanoil.com)*

*Email: [commercial@sepahanoil.com](mailto:commercial@sepahanoil.com)*